芯芒微电子

XINMANG MICROELECTRONICS

POWERHEN

Electronics

产品规格书

MM94R2

D 类功放电感

联系我们 / CONTACT

电话：0755-28088656

手机 / 微信：13823685284


地址：深圳市龙华新区观澜深粮汽车电子特色工业园A2栋3楼

样品申请 · 替代选型 · 批量报价，欢迎来函来电

Leaded Inductors for Class D 插件型数字功放电感

■MM94R2 Series

Features 特点



- The optimal design realizes high quality sound and low distortion.
  高音质、低失真最佳设计
- Small compact, and DIP type.
  小体积，直插类型
- Low radiation noise by magnetically shielded construction
  闭合磁路封装，低辐射
- High current, Low resistance.
  大电流，低电阻
- Operating temperature : -40℃~+125℃.
  工作温度：-40℃~+125℃

Applications 应用

- Suitable as choke for digital amp. Car audio, LCD and PDP TV, 5.1ch Home theater, etc.
  适用于数字功放扼流。如汽车音响， LCD 电视和 PDP 电视， 5.1 声道家庭影院等

Electrical characteristics 电气特性

Part number 料号	Inductance ① 电感量 ±1μH	DCR ② 直流电阻 mΩ max.	SRF ③ 自谐频率 MHz	Isat ④ 直流饱和电流 A typica	Irms ⑤ 温升电流 A typical	
			typical	10% drop	20℃ rise	40℃ rise
MM94R2-702AE	7	21.5	32.8	54	9.8	14.2
MM94R2-103AE	10	26	25.5	45	6.5	9.0
MM94R2-153AE	15	31	21.4	20	6.1	8.2

Remark

①Inductance is measured with a LCR meter Agilent 4284A or equivalent. Test frequency at 10kHz

②DC resistance is measured with keithley 580 Milliohm Meter , or equivalent. Reference ambient temperature 25°C

③SRF measured using an Agilent 4395A network analyzer and an Agilent 16193A test fixture.

④DC current at 25°C that causes the specified Inductance drop from its value without current.

⑤Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

⑥Electrical specifications at 25°C

备注

①感量测试采用 Agilent 4284A 数字电桥或同等仪器；测试频率 100KHz

②直流电阻测试采用 keithley 580 毫欧表或同等仪器；环境温度 25° C

③SRF 使用 Agilent 4395A 网络分析仪和 Agilent 16193A 测试夹具测量。

④直流电流在 25° C，加载导致指定电感从没有电流的值下降。

⑤导致指定温度从 25° C 环境温度上升的电流。 此信息仅供参考，不代表绝对最大额定值。


⑥25° C 时的电气规格

ShenZhen Powerhen Electronic Co.,Ltd


Addr:Floor 3, Building 2, Shenliang Automotive Electronic Industrial Park, Guanlan Town, Shenzhen


Tel:0755-23570008 E-Mail:sales@powerhen.com

Dimensions 结构尺寸



Electrical Characteristic Curve 电气特性曲线






ShenZhen Powerhen Electronic Co.,Ltd

Addr:Floor 3, Building 2, Shenliang Automotive Electronic Industrial Park, Guanlan Town, Shenzhen

Tel:0755-23570008 E-Mail:sales@powerhen.com

■Packaging Specification - tray: [mm]

包装规格 – 托盘包装：[mm]



Weight 重量: 17~20.15g/PCS

Packaging 包装数量: 20 PCS/盘

ShenZhen Powerhen Electronic Co.,Ltd

Addr:Floor 3, Building 2, Shenliang Automotive Electronic Industrial Park, Guanlan Town, Shenzhen

Tel:0755-23570008 E-Mail:sales@powerhen.com